

# Dome HD Series

IK10 IP66 Smart HD IR SD H.264 PoE

- High Definition
- Vandal Resistant IK10
- Environmental IP66
- Smart Analytics
- Long Range IR illuminators
- Internal SD Card Storage
- ONVIF Compliant
- Quad Video Streams

### Camera

Image Sensor 1/3" Progressive Scan CMOS  
 Color: 0.014 lux @ (f/1.4, AGC ON); B/W 0 lux w IR ON  
 Shutter Speed 1/3seg to 1/10,000 seg  
 Slow Shutter Yes  
 Lens 4 mm @ F2.0 (2.8mm, 6mm, 12mm optional)  
 Angle of view 92.5 (2.8mm); 73.1 (4mm); 46 (6mm), 22 (12mm)  
 Lens mount  $\Phi$  12 with E-PTZ Functionality  
 Day/Night IR Cut filter with Auto switch/schedule/trig by alarm  
 Digital Noise reduction 3D DNR & Smart Dynamic Noise Reduction sDMR\*  
 Wide Dynamic Range 120 dB  
 Infrared Range 100 Feet / 30 Meters

### Compression Standards

Video Compression H.264+/H.264/MJPEG  
 H.264 Type Main Profile  
 Video Bit rate 32 Kbps to 16 Mbps  
 Number of Streams 4  
 Audio G.711/G.722/G.726/MP2L2/64kbps(G.711)/16kbps

### Image

Maximum Resolution 1280x960  
 Frame Rate 30 fps (1280x960), (1280x720), (704x576), (640x480)  
 Image Settings Rotate, saturation, brightness, sharpness, contrast  
 Backlight Compensation Yes, Zone configurable  
 Zones of interest Yes up to 12 configurable areas

### Analytics

Smart Features Line crossing/ intrusion detection

### Network

Network Storage NAS (Supports NFS, SMB/CIFS); ANR  
 Alarm Triggers Motion, line crossing, network disconnect, IP conflict  
 Protocols TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP  
 RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS

### Security

IPV6 IPV4 Bonjour  
 Three level user authentication, password authorization, HTTPS and SSH Certificate, IEEE802.1X, basic and digest authentication, watermark, IP address filtering, log-in lockout

### Standards


ONVIF (profile S, G) PSIA, CGI, ISAPI

### Interface

Communication 1 RJ45 10M/100M Ethernet port  
 On-Board Storage Built in micro SD/SDHC/ SDXC slot up to 64GB  
 Alarm 1 alarm I/O  
 Audio 1 audio I/O

### General

Operating Conditions -30C TO 60C, humidity 95% or less (non-condensating)  
 Power 12Vdc +/- 10%, PoE (802.3af) UL/CUL Listed  
 Power Consumption Maximum 5.5 watt  
 IR Range 30 meters / 100 feet  
 Ingress Protection IP 66  
 Impact Protection IEC60068-275Eh,20j; EN 50102; IK10



• Comparable with Bosch iDNR.  
 • Compatible with Bosch Systems ONVIF S  
 • Bosch and iDNR are registered trademarks of Bosch



Ceiling Mount



Pendant Cap



Pendant Mount



Corner Mount Adapt